MINI CURRENT SWITCH CS-610-75

The CS -610-75 series current switch monitors line current for electrical loads such as pumps, conveyors, lighting, heaters or fans and closes the output contacts when the trip point is exceeded. The CS-610-75 has a trip point that is adjustable between 0.75 to 75 Amps by rotating the adjustment pot. A LED illuminates when trip point setting is reached.

The sensor requires no external power as it is totally powered by induction from the AC line being monitored. The switch output is normally open and when the input current exceeds the trip setpoint the switch closes to provide an on/off digital signal to the controller.

SPECIFICATION:


Current Setpoint	Adjustable - 0.75 to 75 Amps
Maximum Input Current	75 Amps continuous
Sensor Power	Self-powered
Output Type	Solid-state mosfet
Output Switch Action	Normally open
Indication	Illuminated status LED
Output Switch Ratings	30 Vac/dc, 500 mA Max.
Von @ 24 Vdc at 500mA	< 50 mV
Frequency	50/60 Hz
Response Time	200 mS Typical
Insulation Class	600 Vac, Insulated conductors
Operating Temperature	15 to 60 °C (5 to 140 °F)
Operating Humidity	5 to 90% RH non-condensing
Wiring Connections	Screw terminal block
	(14 to 22 AWG)
Dimensions	48 x 49 x 21 mm
	1.9 x 1.93 x 0.83 in)
Sensor Aperture	11.4 mm (0.45 in)
Enclosure Material	ABS/PC, UL94 V-0
Agency Approvals	cULus Listed

TYPICAL INSTALLATION:

For complete installation and wiring details, please refer to the product installation instructions.

The CS-610-75 provides mounting tabs to secure the device inside a motor control panel using (2) # screws.

The sensor has a 2 wire connection to the Building Automation System.



600 Vac max 75 Amps max

Greystone Energy Systems, Inc. 150 English Drive, Moncton, NB Canada E1E 4G7 (506) 853-3057 Fax: (506) 853-6014 North America: 1-800-561-5611 e-mail: mail@greystoneenergy.com www.greystoneenergy.com



PRODUCT ORDERING INFORMATION:

CS-610-75

Mini Current Switch, Adjustable

