


AC POWER SUPPLY: 120 VAC TO 24 VAC

PSB40AB10



Panel Mount 40 VA Power Supply, 120 to 24 Vac

PSB100AB10

Panel Mount 100 VA Power Supply, 120 to 24 Vac



* Move internal jumper to "HOT" position if you wish outlets to always be hot otherwise outlets will be switched by main breaker.



REMOVABLE TERMINAL COVER PROVIDED

POWER SUPPLIES

SPECIFICATIONS

- Transformer:** One 40 VA Split-Bobbin (PSB40AB10)
One 100 VA Split-Bobbin (PSB100AB10)
- Primary:** 120 Vac
- Secondary:** 24 Vac, w/ LED Indicator
- Frequency:** 50/60 Hz
- Over Current Protection:** Inherently Limited + Circuit Breaker (PSB40AB10)
Circuit Breaker (PSB100AB10)
- 24 Vac ON/OFF:** On / Off Switch
- Main Breaker ON/OFF:** Switch / Breaker (10 Amp)
(Kills power to entire unit:
Outlets, Aux. Output, & Transformer)*
Total Combined Output 9A

- Mounting:** Panel mount
- Temperature:** 40° C
- Approvals:** Class 2 (UL Approved
UL5085-3), UL916, UL508 for -IC
models, C-UL
- Dimensions:** 5.200" x 5.250" x 3.750"
- Weight:** 2.18 lbs. (PSB40AB10)
3.58 lbs. (PSB100AB10)

- Notes:**
- To order UL508, add "-IC" to end of model number.