

Series Solenoid Pilot Valve

Low Cost, Compact Design, For Use with SAV Angle Seat Valves



The Series PV three-way normally closed electro-pneumatic solenoid pilot valve can be direct mounted to operate the Series SAV Angle Seat Valve actuators. When the solenoid valve receives the electric input signal, it switches the pneumatic supply pressure to the actuator, which moves the valve from the closed to open position, or reversely for normally open valves. When the input to the solenoid valve stops, the pneumatic supply pressure is again blocked, and the valve returns to the normal position. Suitable for use with air or other inert gases, the valve is supplied with a DIN connector, and is fitted with a manual override. Water can also be used as a pilot media provided that a suitable drain line is attached to the exhaust outlet. Select the proper model according to the SAV valve actuator diameter and power requirements.

SPECIFICATIONS

Pilot Media: Air, water, or inert gases. Power Requirements: See model chart. Wetted Materials: Body: Niploy coated brass; Seal: FKM. Maximum Supply Pressure: 150 psig (10.3 bar). Temperature Limits: 14 to 140°F (-10 to 60°C). Actuator Connection: PV1_: 1/8" BSP; PV2_, PV3_: 1/4" BSP. Pilot Media Connection: 1/8" NPT. Coil Consumption: PV1_, PV2_: AC: 9A (res.), 14A (ind.); DC: 6A; PV3_: AC: 15A (res.), 30A (ind.); DC: 10A. Mounting: Banjo connection. Enclosure Rating: IP65 (with DIN connector). Standard Features: Manual override, DIN connector.

		SAV	Dimensions		
		Actuator	Ain	B in	C in
Model	Voltage	Diameter	(mm)	(mm)	(mm)
PV11	240 VAC				
PV12	120 VAC	1-3/4″	1-1/4	3-1/32	1-1/16
PV13	24 VAC		(31.8)	(77.0)	(27.0)
PV14	24 VDC				
PV21	240 VAC				
PV22	120 VAC	2-1/2″	1-3/8	3-1/16	1-1/16
PV23	24 VAC		(35.0)	(77.8)	(27.0)
PV24	24 VDC				
PV31	240 VAC				
PV32	120 VAC	3-9/16″	1-3/8	3-3/4	1-1/16
PV33	24 VAC		(35.0)	(95.3)	(27.0)
PV34	24 VDC				

USA: California Proposition 65 A WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov